

# SONANCE

## INVISIBLE SERIES



### Features:

Sonance Invisible Series speakers invisibly install in almost any standard wood/metal stud wall or ceiling.

The speaker is completely concealed and essentially becomes an integral part of the wall or ceiling surface.

Using planar diaphragm technology, patented Invisible Series speakers radiate sound in a 140° hemispherical pattern with smooth, even coverage throughout its bandwidth.

# SONANCE INVISIBLE SERIES



## Invisible Speakers for Visionary Interiors

Imagine that. The ability to outfit any room or space with ambient sound without creating clutter, distractions, or disruptions to the interior design. It's why **Sonance Invisible Series** loudspeakers complement some of the most prominent and prestigious destinations and properties in the world, from distinctive residences to glamorous resorts and exclusive retail establishments.

Sonance **Invisible Series** proprietary structural and engineering features make it possible to invisibly install the **Invisible Series** speakers in almost any standard wood/metal stud wall or ceiling; the speaker is completely concealed and essentially becomes an integral part of the wall or ceiling surface. Using planar diaphragm technology, patented **Invisible Series** speakers radiate sound in a 140° hemispherical pattern with smooth, even coverage throughout its bandwidth.

**Invisible Series** speakers employ a rigid, flat diaphragm approximately one-half inch thick, that installs into a standard wall or ceiling cavity replacing the equivalent surface area of gypsum board. Contractor personnel then mud and sand the speaker diaphragm into the surrounding drywall. The speaker's radiating surface becomes part of the wall or ceiling surface, completely disappearing. The wall can then be finished with water-soluble materials such as latex paints, using conventional brush-on, roller or airless spray application systems to match any color or decor requirement. **Invisible Series** speakers may also be covered using wallpaper, light-weight vinyl wall coverings and selected textured coatings.

The **Invisible Series'** exclusive installation method makes the speakers truly invisible, allowing you to place the speakers wherever optimal performance dictates, eliminating any concerns over visual aesthetics.



### SA3 Specifications

<b>Tweeter:</b>	48 in <sup>2</sup> (310cm <sup>2</sup> ) planar diaphragm, driven by a 1.02" (26mm) voice coil
<b>Woofers:</b>	50 in <sup>2</sup> (323cm <sup>2</sup> ) low-frequency radiator, driven by a 1" (25mm) voice coil
<b>Frequency Response:</b>	40Hz – 20kHz ±3dB
<b>Impedance:</b>	8 ohms nominal
<b>Power Handling:</b>	80 watts RMS
<b>Sensitivity:</b>	90dB (1w/1 meter)
<b>Dispersion:</b>	140° hemispherical up to 10kHz
<b>Finish:</b>	Primed surface ready for texture & paint
<b>Overload Protection:</b>	Two independent self-resetting gel switches (low-frequency & high-frequency)
<b>Dimensions (W x H x D):</b>	16" x 24" x 3 7/8" (406mm x 610mm x 98mm)
<b>Shipping Weight:</b>	20 lbs (9.0kg) pair



### SA1.5 Specifications

<b>Tweeter:</b>	48 in <sup>2</sup> (310cm <sup>2</sup> ) planar diaphragm, driven by a 1.02" (26mm) voice coil
<b>Woofers:</b>	33 in <sup>2</sup> (210cm <sup>2</sup> ) low-frequency radiator, driven by a 1" (25mm) voice coil
<b>Frequency Response:</b>	50Hz – 20kHz ±3dB
<b>Impedance:</b>	8 ohms nominal
<b>Power Handling:</b>	80 watts RMS
<b>Sensitivity:</b>	88dB (1w/1 meter)
<b>Dispersion:</b>	140° hemispherical up to 10kHz
<b>Finish:</b>	Primed surface ready for texture & paint
<b>Overload Protection:</b>	Two independent self-resetting gel switches (low-frequency & high-frequency)
<b>Dimensions (W x H x D):</b>	16" x 12" x 3 7/8" (406mm x 305mm x 98mm)
<b>Shipping Weight:</b>	12 lbs (5.4kg) pair



### SAW\* Specifications

<b>Woofers:</b>	Two 50 in <sup>2</sup> (323 cm <sup>2</sup> ) low-frequency radiators, each driven by a 1" (25mm) voice coil
<b>Frequency Response:</b>	35Hz – 150Hz ±3dB
<b>Impedance:</b>	8 ohms nominal
<b>Power Handling:</b>	150 watts RMS
<b>Sensitivity:</b>	90dB (1W/1 meter)
<b>Dispersion:</b>	180° hemispherical up to 150Hz
<b>Finish:</b>	Primed surface ready for texture and paint
<b>Overload Protection:</b>	Self-resetting gel switch
<b>Dimensions (W x H x D):</b>	16" x 24" x 3 7/8" (406mm x 610mm x 98mm)
<b>Shipping Weight:</b>	17 lbs (7.7kg) each

\*Requires Sonamp® A800 (available separately)



## SPACE SAVER

Reusable piece installed during new construction to preserve the space until the speaker is installed.

### SA3/SAW SPACE SAVER

<b>Dimensions (W x H x D):</b>	16" x 24" x 3 1/2" (406mm x 610mm x 89mm)
<b>Shipping Weight:</b>	8 lbs (3.6kg)

### SA1.5 SPACE SAVER

<b>Dimensions (W x H x D):</b>	12" x 16" x 3 1/2" (305mm x 406mm x 89mm)
<b>Shipping Weight:</b>	5 lbs (2.3kg)

## Sonance

212 Avenida Fabricante  
San Clemente, CA 92672-7531 USA  
800.582.7777  
sonance.com

©2009 Sonance, All Rights Reserved. Sonance and Sonamp are registered trademarks of Dana Innovations.

Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product information, go to : [www.sonance.com](http://www.sonance.com)